§60.3 (d)(2). Copies of the input and output data from the original and modified computer models must be submitted

- (5) Delineation of the revised floodway on the same topographic map used for the delineation of the revised flood boundaries.
- (c) Data requirements for changes not associated with base flood elevation changes. The following data shall be submitted:
- (1) Items described in paragraphs (b) (1) through (3) of this section must be submitted.
- (2) Engineering analysis for the revised floodway, as described below:
- (i) The original hydraulic computer model used to develop the established base flood elevations must be modified to include all encroachments that have occurred in the flood plain since the existing floodway was developed. If the original hydraulic computer model is not available, an alternate hydraulic computer model may be used provided the alternate model has been calibrated so as to reproduce the original water surface profile of the original hydraulic computer model. The alternate model must be then modified to include all encroachments that have occurred since the existing floodway was developed.
- (ii) The floodway analysis must be performed with the modified computer model using the desired floodway limits
- (iii) The floodway limits must be set so that combined effects of the past encroachments and the new floodway limits do not increase the effective base flood elevations by more than the amount specified in §60.3(d)(2). Copies of the input and output data from the original and modified computer models must be submitted.
- (3) Delineation of the revised floodway on a copy of the effective NFIP map and a suitable topographic map.
- (d) Certification requirements. All analyses submitted shall be certified by a registered professional engineer. All topographic data shall be certified by a registered professional engineer or licensed land surveyor. Certifications are subject to the definition given at §65.2 of this subchapter.

(e) Submission procedures. All requests that involve changes to floodways shall be submitted to the appropriate FEMA Regional Office servicing the community's geographic area.

[51 FR 30315, Aug. 25, 1986]

## §65.8 Review of proposed projects.

A community, or an individual through the community, may request FEMA's comments on whether a proposed project, if built as proposed, would justify a map revision. FEMA's comments will be issued in the form of a letter, termed a Conditional Letter of Map Revision, in accordance with 44 CFR part 72. The data required to support such requests are the same as those required for final revisions under §§ 65.5, 65.6, and 65.7, except as-built certification is not required. All such requests shall be submitted to the FEMA Headquarters Office in Washington, DC, and shall be accompanied by the appropriate payment, in accordance with 44 CFR part 72.

[62 FR 5736, Feb. 6, 1997]

## § 65.9 Review and response by the Administrator.

If any questions or problems arise during review, FEMA will consult the Chief Executive Officer of the community (CEO), the community official designated by the CEO, and/or the requester for resolution. Upon receipt of a revision request, the Administrator shall mail an acknowledgment of receipt of such request to the CEO. Within 90 days of receiving the request with all necessary information, the Administrator shall notify the CEO of one or more of the following:

- (a) The effective map(s) shall not be modified:
- (b) The base flood elevations on the effective FIRM shall be modified and new base flood elevations shall be established under the provisions of part 67 of this subchapter;
- (c) The changes requested are approved and the map(s) amended by Letter of Map Revision (LOMR);
- (d) The changes requested are approved and a revised map(s) will be printed and distributed;
- (e) The changes requested are not of such a significant nature as to warrant